STYROCUT – 3 (24-0300): hot wire cutting for model making applications, also for landscaper modelling Guide bar moves along the side on ball bearings, rear bar lock, opening width 460 mm / 18 lnch,

Cutting height 6 times adjustable 80 to **210 mm** / 3.1 to 8", cutting angle 45° up to 130 mm / 5" height, matt aluminium coated working surface **610 x 265 mm** / 24×10.4 ", two adjustable buffers.

Integrated blower for low-smell working and sharp-edged cutting quality, tool-free handling. In-plug power supply 100-240 VAC 50/60 Hz, sec.12 VAC, adapters: according to your country.

contents : protractor, steel ruler mm/inch, 2 hexagonal spanners, 10-m-spool of cutting wire 0,19 mm / 0.007" Weight about 5.2 kg. Always with pedal switch:	580.00 €
For starting advised: large 40-m-(130 ft)-spool of cutting wire, exchanged for standard spool only more	8.90 €
Angle Cutting Glide (24-0116): angle guide 100 mm with adjustable nose for serial and accurate cutting. Gliding along rip fence or to be moved the other way, when fixed to it.	39.00€
Depth Setting (24-0119): pre-adjustment of cutting depth. Essential for exact serial cutting of notches. This is particularly advisable because of the bending of the cutting wire and its related follow-up effect.	23.00 €
Horizontal Cutter (24-0112): tightens a cutting wire between bracket and rip fence for cutting slices even not parallel. Cutting height up to 120 mm, cutting width up to 300 mm. No danger of wobbling because workpiece lies flat.	38.00 €
Circular Cutter (24-0114): cuts cylinders, cylinder bowls, cones and other shapes. Diameter from 19 to 220 mm and up to about 110 mm height. Rotates 360° due to 1:2 gear ratio without having to change hands.	84.00 €
Long rip fence (24-0118): higher and longer guide for higher and longer workpieces. Attached and dismantled quickly. Size 540 x 50 mm. Specially recommended for Styrocut-3 working range.	29.00 €
Cutting height extension by 70 and 120 mm /2.7" to 4.7" with stronger wire, together with a new Styrocut When ordered separately: with cutting wire 0.25 mm 0.01" and stronger power supply min. 3A – 12V	41.50 € 60.50 €
STYROCUT–3–SET (24-0308) St-3 including Angle Cutting Glide, Depth Setting, Horizontal Cutter, Circular Cutter and Long Rip Fence	790.00 €
Table Extension by front and back rollers (24-0111) 540 mm width, held by two beams. Ball-bearing rolls are attached in front of and behind working surface. Enabling a smooth gliding alongside the rip fence for all workpieces longer than guide bar itself.	58.00 €
10-m-(33 ft)-Spool of Wire (24-0110) Nickel-chrome resistant wire 0.19 mm, to be tightened by cold-stretching	4.60 €
40-m-(130 ft)-Spool of Wire (24-0160) the "long life spool" (with new machine, mounted only 8,90 €)	13.50 €
Pedal Switch in Styrocut-Machines always included, switches power as long as heat is needed 12-V-Version (24-0113) with extension lead, please ask for type of plug / socket 110- 230-V-version (24-0115), for older Styrocut with inbuilt transformer, even US/GB-plug possible	39.00 € 48.00 €
Ell Warranty two years, world warranty and year (agate of appure transportation to be barne by quater	

EU- Warranty two years, world- warranty one year (costs of secure transportation to be borne by customer)

Styrofoam HD 300 (Ravago) dark grey and dense extruded hard foam without visible pores

weight 52 kg /cbm

Block 580 x 330 x 100 mm (23-1033) 22.00 € we ship up to 7 pcs. / parcel

XPS-Foam white extruded hard foam 35 kg/cbm not coloured, less smell

Block 580 x 300 x 80 mm (23-8033) 18.30 € up to 10 pcs. in a parcel

Foam will not be wrapped on small side but sent in 600 mm length. It cannot be complained about for normal shipment damage. Shipping costs will be invoiced separately according to weight and land. We will send a pro-forma-invoice in advance.

Even your up to 35 years old Styrocut is in good hands here, see special offer for total review

If any questions do not hesitate to mail and, please, add fotos for us to identify your problems.

STYROCUT- Johannes Scherffig	Steffenstr. 4	40545 Düsseldorf	Germany
www.styrocut.de	info@styrocut.de	Tel. : + 49	-
	(0)211- 57 48 00		